

DAILY RG 900 KS

GENMAC



MADE IN ITALY

Picture as a way of example only

MODEL	DAILY RG 900 KS
ALTERNATOR	
Type	Synchronous, single phase, brushless, Self Regulated, Self Excited
Voltage - Frequency	230V - 50 Hz
Prime Power	8,8 kW / 9,8 kVA
Max. Power	9,8 kW/ 10,9 kVA
Intensity PRP / LTP	38,3 A / 42,6 A
Protection	IP 23
ENGINE	
Type	Twin -Cylinder, 4 Strokes, air cooled, 3000 rpm
Brand	KOHLER
Model	KD 425/2
Displacement - HP	851 cc / 20
Fuel	DIESEL
Autonomy/ Fuel tank	8 h / 19 lt.
Starting System	ELECTRICAL (battery included)
CONTROL PANEL	
Control Panel	Socket 1x CEE 16A 230V; 2x CEE 32A 230V Thermal breaker, Circuit Breaker, Voltmeter (analogic), Analogic hourmeter, Start/Stop switch, Emergency stop button, 10 PIN socket for remote starting for ATS connection. Engine Protection card RGK30: Low oil pressure protection, High temperature protection, over/underspeed protection, charger alternator failure protection. Battery.
Dimensions mm LxLxA	1030x620x804
Weight - Kgs.	247
Noise Level @ 7m.	72