



DIESEL GENERATOR

FUEL OPTIMISED

**ELECTRICAL**

Frequency (Hz)	Phases	Voltage (V)	Prime		Standby		MCB Rating (A)	Minimum ATP Rating (A)	Rated Speed (RPM)
			kVA	kW	kVA	kW			
50	3	400/230V	500	400	550	440	800	800	1500

**POWER FACTOR**

3 Phase	0.8
1 Phase	1

**MAXIMUM LOAD IMPACT\***

kVA	275
kW	220

\*With 20% voltage and 10% frequency deviation @ 50Hz, 400V

**ALL RATINGS ARE TO STANDARD REFERENCE CONDITIONS ISO 8528**

**Prime:** This rating is for the supply of continuous electrical power, at variable load, in lieu of commercially purchase power. There is no limitation on the annual hours of operation and 10% over load power can be supplied for 1 hour in 12.

**Standby:** This rating is for the supply of continuous electrical power, at variable load, in the event of a utility power failure. No overload is permitted.

**"Stage IIIa"** models are only emissions compliant at 50Hz Prime Power in accordance with 97-68EC.

**JCB GENERATOR TECHNICAL SPECIFICATIONS.**

ЭНЕРГОКОНТИНЕНТ

**CANOPY/SKID**

Lockable Maintenance Access Doors	x
Control Panel Viewing Window	x
Fork Pockets	x
Single Lift Point	x
Rental Sledging Base	x
Bunding	Δ
Open Frame	●
Bund Level Indicator	x
50mm Rock Wool Sound Insulation	x
Yellow Paint	x
Red Paint	x
White Paint	x

Standard: ● Not Available: x Optional: Δ

**ALTERNATOR ECO 40-3S/4**

Poles	4
Winding Connections	Star
Insulation	Class H
Enclosure	IP23
Exciter System	Self-regulating brushless
Voltage Regulator	AVR (electronic)
Steady State Voltage Regulation	+/- 1.0%
Bearing	Single bearing sealed
Coupling	Flexible disc
Cooling	Direct drive centrifugal blower fan
Coating	Winding Protection Grey

**STARTING SYSTEM**

Starter Motor	kW	7.0
Battery Type		656
Number of Batteries		2 (Series)
Auxiliary Voltage	V	24

**ENGINE**

<b>1500 RPM</b>		
Output Rating (PRP)	kW	430
Output Rating (Standby)	kW	473
Manufacturer and Model		Volvo TAD 1641GE
Fuel		Diesel
Injection		Direct
Aspiration		Turbo Charged
Cylinders		6
Bore and Stroke	mm	144 / 165
Displacement	L	16.12
Cooling		Water
Engine Oil Specification		15W/40
Compression Ratio		16.5 : 1
Engine Oil Capacity	L	48
Coolant Capacity	L	44
Governor		Electronic Governor
Air Filter		2 stage paper element
Engine Oil Consumption	100% Load	0.1 ltrs/hr

**FUEL SYSTEM**

Diesel Specification		EN590
Standard Fuel Tank Capacity	L	755

**FUEL TANK OPTIONS**

	Material	Capacity (L)
Standard Tank	Steel	755
Bunded Tank option	Steel	692
Extended Tank option	Steel	1298
Bunded Extended Tank option	Steel	1191

**JCB GENERATOR TECHNICAL SPECIFICATIONS.**

50Hz\_G550S\_EN - Issued: 08/06/2016 13:25:05

ЭНЕРГОКОНТИНЕНТ

**FUEL CONSUMPTION**

100% Load Prime	L/h	50Hz	102.9
75% Load Prime	L/h		76.0
50% Load Prime	L/h		51.4
100% Load Standby	L/h		113.5

**EXHAUST SYSTEM**

Exhaust Gas Temperature	°C	50Hz	455
Exhaust Gas Flow 100% Standby	m <sup>3</sup> /s		1.533
Maximum Allowed Back Pressure	mbar		100
Typical Exhaust Pipe Diameter	mm	200	

**AIR SYSTEM**

Intake Air Flow 100% Standby	m <sup>3</sup> /s	50Hz	0.633
Total Cooling Air Flow 100% Standby	m <sup>3</sup> /s		7.5
Alternator Fan Airflow	m <sup>3</sup> /s		1.08

**SOUND PRESSURE**

LpA (1m)	50Hz	dB(A)	106
----------	------	-------	-----

**MECHANICAL FEATURES**

Cooling Pack	●
Air Filter	●
Mechanical Governor	x
Electronic Governor	●
High Coolant Temperature Sender	●
Low Oil Pressure Sender	●
Advanced Coolant Temperature Sender	x
Advanced Oil Pressure Sender	x
Oil Temperature Sender	x
Water Level Sender	x
Radiator Guards	●
Hot Component Guards	●
Manual Oil Drain Pump	Δ
Water Jacket Heater	Δ
Manual Fuel Fill	Δ
Electric Fuel Fill	Δ
Racor Fuel Filter (No Alarm)	x
Racor Fuel Filter (With Alarm)	x
Pre-Filter with Separator	Δ
External Spark Arrestor	Δ
Fuel Level Sender	●
Fuel Heater	Δ
External Fuel Fill (Belly Tank)	x
3 Way Fuel Valve and Coupling Nest	x
Residential Silencer	Δ
Industrial Silencer	●
Critical Silencer	Δ

Standard: ●      Not Available: x      Optional: Δ

**ELECTRICAL FEATURES**

AVR DSR	●
AVR DER	x
Winding Protection Standard	x
Winding Protection Standard +	x
Winding Protection Grey	●
Winding Protection Total	Δ
Winding Protection Total +	Δ
MAUX	●
PMG	Δ
Anti-Condensation Heater	Δ
Miniature Circuit Breaker (Integrated busbar)	x
Moulded Case Circuit Breaker (with integrated busbar)	●
Earth Leakage Protection (Shunt Trip)	●
Synchronisation	Δ
Socket Box (inclusive of heavy duty busbar & micro switch)	x
Preparation for Earth Spike	●
Optional Voltages	Δ
Remote Screen	Δ
Panel Door Micro Switch	Δ
Copper Busbar/Tails	Δ
Emergency Stop Button	●
External Emergency Stop Button	x
Standard: ● Not Available: x Optional: Δ	

**BATTERY FEATURES**

Battery Isolator	●
Battery Type	Lead-Acid
Battery Size (CCA)	810
Number of Batteries	2
Optional Battery	x
Battery Charger	●
Standard: ● Not Available: x Optional: Δ	

**JCB COMMUNICATION AND CONTROL**

KS1	x
DSE7310	●
DSE7320	Δ
ATS	Δ
USB	●
RS-232	●
RS-485	●
Standard: ● Not Available: x Optional: Δ	

**SYNCHRONISATION PANEL (OPTION)**

DSE8610	Δ
DSE8620	Δ
Standard: ● Not Available: x Optional: Δ	

**WEIGHT AND DIMENSIONS**

Length	mm	3710
Width	mm	1187
Height	mm	2270
Weight*	Kg	5098

\*Standard build with all fluids except fuel

**REFERENCE STANDARDS**

JCB Generators are CE certified and conform to the following Directives (subject to a country requiring such standard):

- EN 12100, EN13857, EN60204
  - 2006/42/CE Machinery safety
  - 2006/95/EC Low voltage
  - 2004/108/CE Electromagnetic compatibility
  - 2000/14/EC Sound Power Level (amended by 2005/88/EC)
  - 97/68/EC Emissions(amended by 2002/88/EC & 2004/26/EC)
  - Power according to ISO 8528 and ISO 3046
  - Ambient reference conditions 1000mbar, 25°C, 30% relative humidity ISO3046
- Information based on standard specification equipment unless otherwise stated.

**JCB GENERATOR TECHNICAL SPECIFICATIONS.**

ЭНЕРГОКОНТИНЕНТ